## 328-3 / 2030TU

## 3/16" BEVERAGE DISPENSING





#### **Gas applications**

#		<b>©</b>		Ó		7			R	Kg	
	DN	size	mm	inch	mm	bar	psi	bar	psi	mm	kg/m
328-3	5	-3	4.7	3/16	9.0	345	5,000	1400	20,000	75.0	0.051
2030TU-04R14V17	5	-4	4.8	3/16	9.0	210	3,000	1840	12,000	51.0	0.09

#### **APPLICATIONS**

High pressure service for use with  ${\rm CO_2}$  (2030TU) and nitrogen (328-3) gas. Specifically used in the beverage dispense industry.

### **FEATURES**

- Flavour free materials suitable for food applications
- FDA approved liner
- Pinpricked cover for gas use
- · A large range of fittings and accessories available
- Private branding available

#### **CONSTRUCTION - 328-3**

Core tube: TEE

**Pressure reinforcement:** One braided layer of high tensile aramid fibre.

Outer cover: TPU black pinpricked.

#### **CONSTRUCTION - 2030TU-04**

Core tube:

**Pressure reinforcement:** One braided layer of stainless steel wire.

Outer cover: TPU grey pinpricked.


### **TEMPERATURE RANGE**

 $-40^{\circ}$ C up to  $+100^{\circ}$ C.

#### **FITTINGS**


#### BSP Male bottle connection nut BS341 No.3

#	<b>©</b>				<u>~~~</u>	Α	В	$\langle H \rangle$
	DN	size	mm	inch		mm	mm	mm
DS-R5/8	5	-03	4.7	3/16	5/8 BSP	28.5	21.0	27




#### 0-ring bottle connection insert to suit 5/8 BSP nut

#		Q	Ď		<u>~~~</u>	Α
	DN	size	mm	inch		mm
ABD244	5	-03	4.7	3/16	Insert	28.0



#### **BSPT Male fixed**

#	<b>©</b>				<u>~~~</u>	Α	В	$\langle H \rangle$
	DN	size	mm	inch		mm	mm	mm
ABD248	5	-03	4.7	3/16	1/8 BSPT	19.3	10.5	12.0
ABD256	5	-03	4.7	3/16	1/4 BSPT	21.5	14.5	14.0





Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.






# **328-3 / 2030TU** 3/16" BEVERAGE DISPENSING


#### **NPT Male fixed**

#					<u>~~~</u>	Α	В	$\langle H \rangle$
	DN	size	mm	inch		mm	mm	mm
K91PX-4-03	5	-03	4.7	3/16	1/4 NPT Male	19.0	14.0	14.0



## ${\rm CO_2}$ Bottle connection insert to suit BS 341 No. 8 nut

#		Q.	Ď		<u>~~~</u>	Α
	DN	size	mm	inch		mm
ABD265	5	-03	4.7	3/16	CO <sub>2</sub> Female Insert	7.2




## CO<sub>2</sub> Female nut BS 341 No.8

#	DN ciza mm linch		<u>~~~</u>	А	⟨ <b>H</b> ⟩		
	DN	size	mm	inch		mm	mm
ABD251	5	-03	4.7	3/16	21.8 Whitworth	21.0	28.0




## CO, Female knurled BS 341 No.8

#	<b>©</b>			Ø				<u>~~~</u>	Α	В
	DN	size	mm	inch		mm	mm			
ABD253	5	-03	4.7	3/16	21.8 Whitworth	70.0	19.5			



## Plastic hand wheel to suit ${\rm CO_2}$ and ${\rm N_2}$ nut

#	<b>O</b>				<u>~~~</u>	Α	(H)
	DN	size	mm	inch		mm	mm
ABD950	-	-	-	-	-	-	28.0





Please Note: Variety of fittings in mild steel or stainless steel available, other fittings available on request. We reserve the right to make technical changes without notice.